





CSL106T

FBT 5" Ceiling Speaker,


Quick Mount spring mechanism with powder coated metal grill, dual-cone 5" woofer, 6W/3W taps at 100V line. Frequency response 100Hz-15kHz, sensitivity @1W/1m 93dB, white colour RAL9016, Dimensions 175x60mm, cut-out hole 150mm, weight 0.5Kg.



CSL630TIC

FBT 6" Ceiling Speaker with Backcan


Powder coated metal grill, iron back cover, coaxial speaker with 6" woofer and 1/2" tweeter, 3.8W/7.5W/15W/30W taps at 100V line, 30W at 8 Ohm. Frequency response 90Hz-20kHz, sensitivity @1W/1m 88dB, white colour RAL9016. Dimensions 230x150mm, cut-out hole 200mm, weight 2.3Kg.



CSL840TIC

FBT 8" Ceiling Speaker with Backcan

Powder coated metal grill, iron back cover, coaxial speaker with 8" woofer and 1/2" tweeter, 5W/10W/20W/40W taps at 100V line, 40W at 8 Ohm. Frequency response 50Hz-20kHz, sensitivity @1W/1m 88dB, white colour RAL9016. Dimensions 270x185mm, cut-out hole 240mm, weight 3.1Kg.



CSL606TWP

FBT Water Resistant IP55 rated Ceiling speaker

5" speaker with 1" coaxial tweeter. Moulded plastic cone, plastic basket and grill (RAL 9016 white) making it corrosion resistant and water resistant. Perfect for outdoor use or on boats, pool areas, solariums and damp locations. 20W at 100V line. Sensitivity 90dB @1m/1W, frequency response 95-20KHz. Dim.165x115, recess hole for mounting 122mm. Weight 0.7Kg.

