Plena All-in-One Call Station

www.boschsecurity.com





- Stylish, high-quality six-zone Call Station for the Plena All-in-One System
- Six-zone selection keys with LED indicators, and an 'all-call' key
- Momentary Press To Talk (PTT) key
- Configurable gain, speech filter, limiter, and output level for improved intelligibility
- ▶ Configurable attention chime

The Plena All-in-One Call Station is a stylish, high-quality call station that comprises a stable metal base, a flexible microphone stem, and a unidirectional condenser microphone. It has six zone keys and a separate all-call key for easy selection of zones in a Plena All-in-One public address system. A large 'Press To Talk' (PTT) key, with re-dial function, is used to control the call.

In addition to tabletop use, the special design allows the Call Station to be neatly flush-mounted in a desktop. Up to six Call Stations can be connected in a loop-through arrangement to the same All-in-One Unit, with configurable priority.

Functions

The Call Station supports the selection of six zones and has selectable gain, a selectable speech filter, and a limiter for improved intelligibility. The Call Station has a balanced line-level output, which means it can be positioned up to 600 meters from the Plena All-in-One Unit, by using a Cat-5 cable.

Built-in programming modes are used to select the speech filter, the microphone gain settings, and the Call Station ID. A concealed rotary control at the base

of the Call Station is used to set the output level attenuation. LEDs on the Call Station show which zones have been selected.

An additional LED gives visible feedback on the active state of the microphone and the system:

- Green flashing indicates that the system is in standby (a chime is sounded)
- Green indicates that the microphone is active
- Amber indicates that the system is occupied by another higher priority call

Controls and indicators

- Power on LED
- Press To Talk (PTT) key
- PTT status LED
- Six zone selection keys
- Six zone selection LEDs
- All-call key
- Concealed rotary volume control

Interconnections

- RJ45 system connector
- RJ45 loop-through connector

Certifications and approvals		
Safety		IEC/EN 60065
EMC		EN 55103-1 EN 55103-2 EN 61000-3-2 EN 61000-3-3
Environment		EN 50581
US		UL 60065 FCC Part 15B
CA		CSA C22.2.60065
CN		CCC
AU/NZ		C-Tick
Region	Certification	

Europe

Parts included

Quantity	Component	
1	All-in-One Call Station	
1 m	Cat-5 cable with RJ45 plugs	
1	Terminator plug	

CE

Technical specifications

Electrical

Power Supply	
Voltage	24 Vdc (24 Vdc supplied by PLN-6AIO240)
Current consumption	<50 mA
Performance	
Nominal acoustic sensitivity	85 dB SPL @ 1 kHz (gain preset 0 dB)
Nominal output level	1 V
Input sound level (max.)	110 dB SPL
Gain preset	
Limiter threshold	1 V
Compression ratio limiter	1:20
Distortion	<2% (maximum input)
Input noise level (equiv.)	25 dBA SPL
Frequency response	100 Hz to 14 kHz +/-6 dB
Speech filter	-3dB @ 315 Hz, high-pass, 6 dB/oct
Output impedance	200 ohm

Selections				
Chimes	1-, 2- or 4-tone chime selected on Call Station			
Mechanical				
Base dimensions (H x W x D)	55 x 108 x 240 mm (1.57 x 3.97 x 9.25 in)			
Weight	Approx. 0.5 kg (1.1 lb)			
Mounting	Tabletop			
Color	Charcoal with silver			
Stem length with microphone	390 mm (15.35 in)			
Connection	2 x RJ45, Cat-5, max. length 600 m			
Environmental				
Operating temperature	-10°C to +45°C (14°F to +113°F)			
Storage temperature	-40°C to +70°C (-40°F to +158°F)			
Relative humidity	<95% (non-condensing)			

Ordering information

Plena All-in-One Call Station

Call station for six zones with unidirectional microphone and attention chimes. Order number **PLN-6CS**

Represented by:

Americas:

Americas: Bosch Security Systems, Inc. 12000 Portland Avenue South Burnsville MN 55337, USA Phone: +1-800-392-3497 Fax: +1-800-955-6831 audiosupport@us.bosch.com www.boschsecurity.com

Europe, Middle East, Africa: Bosch Security Systems B.V. P.O. Box 80002

P.O. Box 80002 5617 BA Eindhoven, The Netherlands Phone: + 31 40 2577 284 Fax: +31 40 2577 330 emea.securitysystems@bosch.com www.boschsecurity.com

@ Bosch Security Systems 2014 | Data subject to change without notice 9986566155 | en, V2, 27. Nov 2014

Asia-Pacific:

Asia-Pacific: Robert Bosch (SEA) Pte Ltd, Security Systems 11 Bishan Street 21 Singapore 573943 Phone: +65 6571 2808 Fax: +65 6571 2609 apr.securitysystems@bosch.com www.boschsecurity.asia

China:

China: Bosch (Shanghai) Security Systems Ltd. 201 Building, No. 333 Fuquan Road North IBP Changning District, Shanghai 200335 China Phone +86 21 22181111 Fax: +86 21 22182398 www.bacsbecurity.com.cn www.boschsecurity.com.cn

America Latina:

America Latina: Robert Bosch Ltda Security Systems Division Via Anhanguera, Km 98 CEP 13065-900 Campinas, Sao Paulo, Brazil Phone: +55 19 2103 2860 Fax: +55 19 2103 2862 Iatam.boschsecurity@bosch.com www.boschsecurity.com