



# MI-58R ISM Digital Stereo Bodypack Receiver

## Features

- The MI-58 Series is a digital IEM system operating in ISM 5.8 GHz band, due to the wider bandwidth property, the frequency response range is expanded to 20 Hz~23 kHz, and the S/N ratio is greatly improved, the audio latency is reduced, the sound quality is superior to the UHF system, and has an affordable price. It provides an optional DANTE interface.
- The MI-58 Series consists of the MI-58R stereo bodypack receiver, the MI-58T stereo transmitter and optional noise isolating earphones. Featuring a user-friendly control panel, long-distance transmission, it's ideal for personal and professional stages monitoring and conference language interpretation.
- The MI-58R has Stereo / Mono / Mixed output modes and EQ settings to suit the users' preferences. A Ø 3.5 mm TRS jack provides left/right 100 mW @16 Ω output for earphones. Optional standard or professional Ø 3.5 mm TRS noise isolating earphones are available.



## Specifications

Housing	Industry's smallest, reinforced plastic case.
Display	Backlit graphic LCD.
Frequency Range	ISM 5.8 GHz (5,725 ~ 5,850 MHz)
Modulation Type	Digital modulation
Channel Setting	ACT sync
Receiving Mode	True diversity receiving
Frequency Response	20 Hz ~ 23 kHz (stereo)
Stereo Separation	> 100 dB
Max. S/N Ratio	> 105 dBA (stereo)
T.H.D	0.03% (min) at 1 kHz
Sensitivity	5 μV input level, S/N > 100 dB (stereo).
Earphone Jack	Ø 3.5 mm stereo phone jack, Left / Right × 100 mW @ 16 Ω.
Power Supply	ICR18500 Li-ion rechargeable battery × 1. Current drain 165 mA.
Charger	MP-8 one-slot charging station
Optional Accessories	E-8S or E-8P earphones
Dimensions	63 × 85 × 26 mm (W×H×D)
Weight	Approx. 75 g
Note	Refer to the actual product in the event of product discrepancy.



### MIPRO Electronics Co., Ltd

Headquarters: 814 Beigang Road, Chiayi, 600079, Taiwan  
 Tel: +886.5.238.0809 | Fax: +886.5.238.0803  
 www.mipro.com.tw | mipro@mipro.com.tw