



Front



Back

# DN-202WT

## Wireless Audio Transmitter

For applications where unsightly cable runs or drilling of holes is not permissible, the DN-202 WT and WR combination is ideal for getting stereo audio from point A to B. The DN-202WT is a wireless audio transmitter with balanced XLR and ¼-inch inputs, enabling users to send audio from a professional audio mixer or source through walls and ceilings up to 100 feet (30m) away. The DN-202WR is the companion receiver, featuring balanced XLR and ¼-inch outputs for connection to loudspeakers or amplification systems. Multiple DN-202WR's may be used with a single DN-202WT to optimize sound coverage at an event or split indoor/outdoor/multi-level venues.

### Features

- For use with DN-202WR
- Sends audio up to 30m (100 ft) without wires
- XLR and 1/4" audio inputs
- Able to broadcast to multiple receivers (sold separately)
- External, articulating antennas ensure optimum transmission and reception
- Perfect for event spaces, houses of worship, entertainment venues, education, retail, and more

### Specifications

Frequency Response  
20 Hz – 20 KHz, +3 dB

Signal-to-Noise Ratio  
> 80 dB

THD  
< 0.1%

Input Level  
+5 dBu

Dynamic Range  
> 90 dB at 1 KHz

Crosstalk  
> 90 dB at 1 KHz

Latency  
20 ms

### Wireless Specifications

Channel: 25  
Modulation: GFSK  
Bandwidth: > 1.8 MHz  
Transmission Frequency: 2.404 – 2.476 GHz  
Transmission Range: Up to 100 ft. (30.5 m)  
Transmission Power: 10 dBm

Power  
100–240 V AC, 50/60 Hz  
5 V DC, 3 A, center-positive (adapter included)

Dimensions (width x depth x height)  
5.8" x 4.6" x 1.8"  
149 x 117 x 45 mm

Weight  
1.3 lbs.  
0.6 kg