



DN-2051O 6.5", 2-Way Passive Indoor/Outdoor Speaker

Key Features:

- 2-way design 6.5" woofer and 1" tweeter
- 70V/100V/8Ω operation
- Power handling: 50W (RMS), 100W (PMPO)
- Transformer taps at 100V (20W, 40W, 8 Ω) and 70V (10W, 20W, 40W, 8Ω)
- Weather-resistant design for exterior use
- · Paintable white cabinet and grille
- Adjustable angle wall-mount bracket included

Overview:

The DN-205IO is a 6.5", 2-way passive indoor-outdoor speaker for installations in restaurant patio areas, outdoor bar vignettes, health clubs, outdoor pool areas, and other applications where outdoor music and paging is required. The DN-205IO is weather-resistant and includes a bracket for mounting. For maximum flexibility, each speaker is compatible with $70V/100V/8\Omega$ systems by having an adjustable tap. The speaker binding post screw terminal wire connection accepts larger diameter wire for 8Ω use along with smaller diameter 70V/100V wire. The adjustable horizontal/vertical mounting bracket attaches to the top and bottom of the speaker and to the mounting surface.

Specifications:

- Drivers
 - Low-Frequency Driver: 6.50" (165.5mm)
 - High-Frequency Driver: 1" (25mm)
- Power: 50W RMS
- Impedance: 8Ω
- Transformer Taps: 70V, 100V
- Frequency Response: 60 Hz 20 kHz
- Sensitivity: 86 dB ± 2 dB (1W/1m)
- Dimensions (W x H x D): 5.43" x 11.65" x 7.12" (138 x 296 x 181mm)
- Weight: 9.17 lbs (4.16 kg)