



TECHNICAL SPECIFICATIONS

SPECIFICATION

Input and Output Transmitter	
Input	1x HDMI
Input Connectors	1x 19-pin type-A female HDMI
Output	1x HDMI; 1 CAT Connector
Output Connector	1x 19-pin type-A female HDMI (Loop out), RJ45
Control	1x IR IN; 1 IR OUT
Control Connector	2x 3.5mm mini jacks

Input and Output Receiver	
Input	CAT Connector
Input Connectors	RJ 45 Connector
Output	1 x 19-pin type-A female HDMI
Output Connector	1x 19-pin type-A female HDMI
Control	1x IR IN; 1 IR OUT
Control Connector	2x 3.5mm mini jacks

General	
Video Resolution	Up to 4K@60Hz 4:4:4, HDR
Transmission Distance	4K/1080p ≤ 70m
HDMI Standard	HDMI 2.0; HDCP 2.2 compliant
EDID Management	BUILT-IN EDID
Power Supply	Input: 100VAC~240VAC, 50/60Hz; Output: 12VDC 1A
Power Consumption	4W (Max)
Work Temperature	-5°C ~ 55°C
Relative Humidity	10% - 90%
Dimensions (W*H*D)	80mm x 16.8mm x 80mm
Weight	Transmitter: 70g; Receiver: 70g

