




BOSCH

Invented for life

BCS-CS Series EasyFit Ceiling Loudspeaker



- In 8"
- Choice of power rating: 5W, 10W, 15W
- Wide bandwidth for music reproduction
- Wide dispersion for speech intelligibility
- Simple output-level selection
- Easily flush-mounted in ceilings or bulkheads
- Dependable rota-clamp fixing system
- Blends in with virtually all interiors

The BCS-CS Series of Ceiling Loudspeakers are part of the latest 'EasyFit' range. BCS-CS Loudspeakers are lightweight, quick and easy to install, and are finished in unobtrusive white with an attractive metal grille. Their wide frequency range and dispersion ensure good quality music reproduction and excellent speech intelligibility.


BCS-CS8E 15W 8" Ceiling loudspeaker

Installation

The BCS-CS assembly can be simply and quickly installed into a hole in the ceiling cavity, being secured by four lead-screw rota-clamps. The package includes a circular cut-out template, and a grill removal tool for quick access to the installation screws.

Design

The BCS-CS uses a single-piece dual-cone loudspeaker. A 100V matching transformer is mounted directly on the rear of the frame. Connections are made using a screw terminal block designed for loop-through wiring. The BCSCS series can be connected with or without the series capacitor, making it compatible with legacy equipment and with newer systems designed to AS60849 EVAC standards.



2 | BCS-CS5 Ceiling Loudspeaker

Technical Specifications

Ordering Information

SKU	Model	Description
010426	BCS-CS8E	- MOQ Box of 8 CEILING SPEAKER, EASYFIT 15W 8"

BCS-CS8/15

Driver:	8"
Maximum/rated power:	22W/15W
Power taps:	15, 10, 5, 2.5, 1.25 W
Frequency Range (-10dB):	50Hz - 17kHz
Axial sensitivity, 1W/1m/1kHz:	93dB SPL
Axial SPL at rated power:	105dB @ 1m/1kHz
Opening angle (-6dB):	165° at 1kHz
Ceiling cutout diameter:	238mm
Overall dimensions, Dia x h:	273mm x 103mm
Safety:	acc to EN 60065