

SOLARO XC-SUB

Solaro XC-SUB is a 2x2 (send/receive) USB audio card for Solaro Series processors. It offers volume and mute status sync for Microsoft Teams and connects over a USB 2.0, Class 1 Audio Type B female connector. Solaro XC-SUB is an essential for conferencing, education and hybrid applications demanding high quality computer-based audio, leveraging Xilica proprietary signal processing algorithms and HearClear acoustic echo cancellation.

TECHNICAL SPECIFICATIONS

Electrical

Channel(s)	Two input, two output
Interface	USB 2.0, Class 1 Audio
Bit-Depth	16 bit
Sampling Rate	48kHz
USB Audio Profile(s)	1 × 1 – Speakerphone (HFP host, AEC disabled) 1 × 1 – Speakerphone (HFP host, AEC enabled) 2 × 2 – General line in/out soundcard (A2DP)
USB HID/OS	Control integration for mute, volume sync with Windows and Mac OS Mute status sync for Microsoft Teams
Connector(s)	USB Type B female

Mechanical

Card Slot(s) Occupied	Dual (2)
Shipping Weight	0.275lbs / 0.125kg

General

Compatible Product(s)	Solaro FR1, Solaro FR1-D, Solaro QR1, Solaro XIO 16
Warranty	Xilica Five Year Limited Warranty
Part Number(s)	2200-001-0703